

Web Sling Shackle Crosby S-281

Product information

The Crosby Web sling Shackle S-281 is designed to connect synthetic web slings and synthetic round slings to eyebolts, pad eyes and lifting luss.

Standard: Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these shackles meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

Material: All alloy construction.

Marking: According to standard, CE-marked, Each shackle has a Product Identification Code (PIC) for material traceability along with a Working Load Limit and the name Crosby forged into it.

Standard: EN 13889

Safety factor: 5:1

Part Code	WLL ton	Web slings* Webbing width mm	Web slings* Eye width mm	Web slings* Ply	A mm	C mm	D mm	E mm	K mm	M mm	N mm	Weight kg	Delivery time
420100300230	2.95	50	50	2	26.9	63.5	19.1	41.1	31	97.5	85	0.54	10
420100410230	4.08	75	35	2	31.8	51	22.4	38.1	35.8	86	101	0.68	10
420100570230	5.67	100	50	2	36.6	63.5	25.4	51	41.1	107	114	1.13	10
420100770230	7.7	150	75	2	42.9	92	28.7	70	46.7	143	130	1.95	10

Blueprint

