



Open Spelter Socket McKissick G-416

Product information

Standard: Fed Spec RR-S-550D TYPE A.

Features: Spelter socket terminations have an efficiency rating of 100%, based on the catalogue strength of wire rope.

Material: Forged steel sockets through 1 1/2", cast alloy steel 1-5/8" through 4".

Marking: ID code and Manufacturer's symbol.

Finish: Galvanised.

Safety factor: 5:1

Part Code	Rope Ø range mm	WLL ton	Finish	Rope dia. inch	A mm	C mm	D mm	F mm	G mm	H mm	J mm	L mm	M mm	N mm	Weight kg	Delivery time
122101000062	8-10	12	Galvanized	5/16 - 3/8	123	20.6	20.6	12.7	20.6	42.9	57	44.5	38.1	11.2	0.59	10
122101300062	11-13	20	Galvanized	7/16 - 1/2	141	25.4	25.4	14.2	23.9	47.8	63.5	51	47.8	12.7	1.02	10
122101600062	14-16	27	Galvanized	9/16 - 5/8	171	31.8	30.2	17.5	28.7	57	76	63.5	57	14.2	1.863	10
122101800062	18	43	Galvanized	3/4	202	38.1	35.1	20.6	31.8	66.5	89	76	66.5	15.7	2.64	10
122102200062	20-22	55	Galvanized	7/8	235	44.5	41.4	23.9	38.1	82.5	102	89	79.5	20.3	4.438	10
122102600062	24-26	78	Galvanized	1	268	51	51	28.7	44.5	95.5	114	102	95.5	22.4	7.03	10
122103000062	28-30	92	Galvanized	1 1/8	300	57	57	31.8	51	105	127	117	105	25.4	9.75	10
122103500062	32-35	136	Galvanized	1 1/4 - 1 3/8	335	63.5	63.5	38.1	57	121	140	127	121	28.7	14.1	10
122103800062	38	170	Galvanized	1 1/2	384	76	70	41.4	70	133	152	152	137	30.2	21.4	10
122104200062	40-42	188	Galvanized	† 1 5/8	413	76	76	44.5	76	140	165	165	146	33.3	24.9	10
122104800062	44-48	268	Galvanized	† 1 3/4 - 1 7/8	464	89	89	51	79.5	162	191	178	165	39.6	37.2	10
122105400062	50-54	291	Galvanized	† 2 - 2 1/8	546	102	95.5	57.2	95.5	187	216	229	178	46	59	10
122106000062	56-60	360	Galvanized	† 2 1/4 - 2 3/8	597	114	108	63.5	102	210	229	254	197	54	76	10
122106700062	64-67	424	Galvanized	† 2 1/2 - 2 5/8	648	127	121	73	114	235	248	274	216	60.5	114	10
122107300062	70-73	511	Galvanized	† 2 3/4 - 2 7/8	692	133	127	79	124	267	279	279	229	73	143	10
122108000062	75-80	563	Galvanized	† 3 - 3 1/8	737	146	133	86	133	282	305	287	241	76	172	10

Blueprint

