

## **Fast Connector Socket FCS - with bolt**

## **Product information**

Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Can be used to terminate all constructions of wire rope including high performance ropes, anti-rotation ropes and standard 6 strand ropes.

The connector has to be moulded/casted on the steel wire rope with wirelock resin.

Features: Designed for use with mobile cranes.

Material: Quenched and tempered cast steel.

Finish: Blue painted or hot dip galvanized.

Warning: Compare the spelter's and the wire rope's minimum breaking load.

| Part Code    | Code      | Rope Ø range<br>mm | MBL | Finish  | TB<br>mm | TL<br>mm | A<br>mm | B<br>mm | C<br>mm | Ø H<br>mm | Ø P<br>mm | T<br>mm | W<br>mm | D<br>mm | Ø D<br>mm | Ø J<br>mm | K<br>mm | Weight<br>kg | Delivery time |
|--------------|-----------|--------------------|-----|---------|----------|----------|---------|---------|---------|-----------|-----------|---------|---------|---------|-----------|-----------|---------|--------------|---------------|
| 122101300155 | FCS 701 B | 11-13              | 20  | Painted | 80       | 150      | 62      | 61      | 27      | 15        | 25        | 12      | 25      | 50      | 33        | 49        | 46      | 1.6          | 10            |

## Blueprint

